




ECR International

PRODUCT DIMENSIONS & SPECIFICATIONS

C1318-601VAR Matched

MODEL CC - CASED UPFLOW/DOWNFLOW COILS



STANDARD SPECIFICATIONS

- Rifled copper tubing, enhanced aluminum fins.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- **Right-hand refrigerant and plumbing connections.**
- **Liquid line - 3/8" ODS, suction line - 7/8" ODS.**
- Externally mounted flowrater body with Schrader valve for hiss-testing.
- Embossed galvanized cabinets standard. Cabinets feature furnace connectors (patent pending).
- Split access doors in front for easy service.
- Fully insulated cabinets with faced insulation.
- Five-year limited hassle free warranty.
- ARI certified with ECR brands of A/C and heat pump systems.
- ETL listed.

OPTION CODES:

066 - Same as standard except: Powder coated galvanized metal drain pan with double drain; flanged top duct opening.

Unit shown with service panels removed. Representative drawing only. Some models may vary in appearance.

COIL MODEL	CAPACITY (Tons)	FLOW RATER SIZE	ALL DIMENSIONS IN INCHES							WEIGHT (LBS)
			CABINET WIDTH (W)	CABINET DEPTH (D)	CABINET HEIGHT (H)	PLENUM WIDTH (W)	PLENUM DEPTH (D)	BOTTOM OPENING (W)	BOTTOM OPENING (D)	
CC24A3F-220R-066	2	0.059	22	21-1/2	16	20-1/2	20	21-1/4	20-3/4	37
CC30C3F-220R-066	2-1/2	0.068	22	21-1/2	20	20-1/2	20	21-1/4	20-3/4	56
CC36B3F-220R-066	3	0.074	22	21-1/2	20	20-1/2	20	21-1/4	20-3/4	56
CC42C3F-220R-066	3-1/2	0.080	22	21-1/2	24	20-1/2	20	21-1/4	20-3/4	69
CC48B3F-220R-066	4	0.084	22	21-1/2	24	20-1/2	20	21-1/4	20-3/4	69
CC60D3F-220R-066	5	0.092	22	23	28	20-1/2	21-1/2	21-1/4	22-1/4	91
CC60D3F-260R-066	5	0.092	26	23	28	24-1/2	21-1/2	25-1/4	22-1/4	91

C	A	24	A3	F	-145	L	-1
C Series Configuration		Nominal tonnage (MBTUH)		Coil descriptor code (face area, rows, fpi)		Option Code	
A = uncased up/down B = cased dedicated horizontal LaborSaver C = cased up/down D = full depth cased downflow E = cased multi-position VersaCoil P = cased dedicated horizontal with attached Plenum						Refrigerant and plumbing connections L = left-hand plumbing and refrigerant connections R = right-hand plumbing and refrigerant connections T = refrigerant out the top, plumbing out opposite sides CA Series: Drain pan width code CB, CC, CD, CE, CP Series: Furnace width code Metering device F = Flo-ratoer B = 20% bleed A/C or H/P R22 TXV X = non-bleed A/C or H/P R22 TXV 4 = non-bleed A/C or H/P R410 TXV	

ECR International Ltd • P.O. Box 900 • 6800 Base Line • Wallaceburg • Ontario • N8A 5E5 • 519-627-0791

Ecr International • P.O. Box 4729 • 2201 Dwyer Ave • Utica • New York • 13504 • 716-366-5500

www.ecrinternational.com